

Hykers

Filtration



空氣淨化玻璃纖維蓬鬆過濾毡

(Bulky Fiberglass Filter Felt for Air Cleaning)

簡介：

該產品是由玻璃纖維製成，呈蓬鬆狀態。因此其容塵量大，使用周期長，是初效空氣過濾用的優良材料。

性能：

- ▲外觀：表面為綠色和白色蓬鬆體或兩面均為白色的蓬鬆體
- ▲厚度：30mm, 50mm, 100mm (其它規格的厚度可根據客戶要求加工製作)
- ▲寬度：300 - 2100mm
- ▲密度：3 - 8kg/m³

Introduction

The product is made of fluffy glass fibers and has advantages of high dust holding capacity and long cycle life. It is an ideal material for primary air filtration.

Specification

- ▲Appearance: Bulky mass with green and white (or both white) surfaces.
- ▲Thickness: 30mm, 50mm, 100mm (Special sizes are available on request.)
- ▲Width: 300-2100mm
- ▲Density: 3-8kg/m³

型號 Type	自由狀態厚度(mm) Free state thickness(mm)	不同風速(m/s)時的阻力Pa Pressure drop at different air flow rate (Pa)			不同粒徑下的平均效率% Efficiency vs particle size(%)			容塵量(g/m ²) Dust holding capacity (g/m ²)
		1.3	2.6	3.9	≥2 μ	≥5 μ	≥10 μ	
PS-30	30	15	29	44	31	62	71	1100
PS-50	50	16	31	47	35	68	80	1850
PS-100	100	23	41	54	57	81	92	3200

用途：

該產品可廣泛用於鋼鐵、電子、化工、汽車、環保和電力等行業，以及各種空調系統的除塵除油粗過濾。

包裝：

以捲材形式供應或加工成一定尺寸的塊狀，捲材外用透明塑料袋再用編織袋包裝。

Application

Widely used for course filtration of air and oil in iron and steel, electronic, chemical, automobile, environment and power Industries as well as various air-conditioning systems.

Packing

The product is supplied in rolls or cut-to-size blocks. Rolls are packed in transparent plastic bags, which are contained in woven bags.

